

## SB-188 HIGH TEMPERATURE SILICONE SEALANT (CLEAR)

### SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Page Number: 1/6  
Revision Date: 11/20/2015

**Product Name:** SB-188 HIGH TEMPERATURE SILICONE SEALANT (CLEAR)  
**Company Name:** SUREBOND  
3925 Stern Avenue  
St. Charles, IL 60174  
Phone: (877) 843-1818  
**Emergency Phone (24 hour):** CHEMTREC  
(800) 424-9300  
**Chemtrec (outside USA):** (703) 527-3887

### SECTION 2 - HAZARDS IDENTIFICATION

**GHS Classification:** Not a hazardous mixture  
**GHS Label elements:** Not a hazardous mixture  
**Hazard symbols:** None  
**Signal word:** None  
**Hazard statements:** None  
**Precautionary statements:**  
**Prevention:** P271 Use only outdoors or in a well-ventilated area.  
**Response:** Not applicable  
**Storage:** Not applicable  
**Disposal:** Not applicable  
**Other hazards:** None known  
**Supplemental information:** 95% of the mixture consists of component(s) of unknown acute inhalation toxicity.

### SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

**Substance/Mixture:** Mixture

Chemical Name	CAS Number	Concentration (%)
Silicone Dioxide	7631-86-9	5.0 – 10.0
Distillates (Petroleum), Hydrotreated Middle	64742-46-7	5.0 – 10.0

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to the health or the environment and hence require reporting in this section.

### SECTION 4 - FIRST AID MEASURES

**Eyes:** Flush with copious quantities of lukewarm water for at least 15 minutes. Do not attempt to physically remove the solids or gums from the eye. Seek medical attention immediately if irritation persists.  
**Skin:** Remove contaminated clothing. Wash thoroughly with warm water and non-abrasive soap. Seek medical attention if you feel ill or a reaction develops.  
**Inhalation:** Remove to fresh air and provide water. Seek medical attention if you feel ill or a reaction develops.  
**Ingestion:** Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention.

## SB-188 HIGH TEMPERATURE SILICONE SEALANT (CLEAR)

Most important symptoms and effects, both acute and delayed:

None known.

Page Number: 2/6  
Revision Date: 11/20/2015

Indication of any immediate medical attention and special treatment needed:

Provide general supportive measures and treat symptomatically.

### SECTION 5 - FIRE FIGHTING MEASURES

Suitable extinguishing agents:

Carbon dioxide, dry chemical, water fog or foam.  
Water can be used to cool fire exposed containers.

Unsuitable extinguishing agents:

None known

Special hazards arising from the chemical:

Exposure to combustion products such as carbon oxides, silicone oxides and formaldehyde may be hazard to health.

Special protective equipment and precautions for fire fighters:

Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan.

### SECTION 6 - ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures:** Follow safe handling advice and personal protective equipment recommendations in Section 8.

**Environmental precautions:** Discharged into the environment must be avoided. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

**Methods and material for containment and cleaning up:** Restrict access to the area of the spill. Provide ventilation, NIOSH/MHSA approved respirator and protective clothing. Scrape up sealant and place in container for disposal. Clean area as appropriate since silicone materials can represent a slip hazard. Cleaning may require steam, solvents or detergents. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur. Local, state, provincial, federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup.

### SECTION 7 - HANDLING AND STORAGE

**Precautions for safe handling:**

- Handle in accordance with good industrial hygiene and safety practice.
- Take care to prevent spills, waste and minimize release to the environment.

**Conditions for safe storage, including any incompatibilities:**

- Store in an adequately ventilated area under dry conditions between 50°F (10°C) to 77°F (25°C)
- Keep container tightly sealed when not in use.
- Do not store with strong oxidizing agents.

### SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters:**

Ingredient	CAS No.	Value Type (form of exposure)	Control parameters/ Permissible concentration	Basis
Silicone Dioxide	7631-86-9	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m <sup>3</sup> /%SiO <sub>2</sub> (Silica)	OSHA Z-3
		TWA	6 mg/m <sup>3</sup> (Silica)	NIOSH REL

(Continued next page...)

## SB-188 HIGH TEMPERATURE SILICONE SEALANT (CLEAR)

Page Number: 3/6  
Revision Date: 11/20/2015

Distillates (Petroleum), Hydrotreated Middle	64742-46-7	TWA (Mist)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Mist)	5 mg/m <sup>3</sup>	OSHA P0
		TWA (Mist)	5 mg/m <sup>3</sup>	NIOSH REL
		ST (Mist)	10 mg/m <sup>3</sup>	NIOSH REL

**Engineering controls:** Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations. Use respiratory protection unless local exhaust ventilation is provided or exposures are within guidelines.

**Personal protective equipment:** Safety glasses with side-protection, impermeable gloves (e.g., neoprene, nitrile, silver shield (R)), coveralls or apron are important in preventing contamination of eyes, skin and clothing. Wash thoroughly after handling.

### SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Paste, colorless

**Odor:** Acetic acid

**Odor Threshold:** Not available

**pH (ASTM D1293):** 3.2

**Melting Point/Freezing Point:** Not available

**Initial boiling point and boiling range:** Not available

**Flash Point:** >212°F (100°C) Closed Cup Method

**Evaporation Rate:** Not applicable

**Flammability (solid, gas):** Not classified as a flammability hazard

**Upper flammability or explosion limit:** Not available

**Lower flammability or explosion limit:** Not available

**Vapor pressure:** Not applicable

**Vapor density:** Not available

**Specific gravity:** 1.01

**Solubility:** Not available

**Partition coefficient (n-octanol/water):** Not available

**Auto-ignition temperature:** Not available

**Decomposition temperature:** Not available

**Viscosity:** Not applicable

**Acid Reserve, g NaOH/100 g (CCCR 2001, Sections 43 and 44):** 0.17

**Volatile Organic Content:** 30 grams per liter, <3% by weight (Chemically Curing Sealants and Caulks – CARB Method 310: VOC less water, less exempt compounds and LVP-VOCs).

## SB-188 HIGH TEMPERATURE SILICONE SEALANT (CLEAR)

### SECTION 10 - STABILITY AND REACTIVITY

Page Number: 4/6  
Revision Date: 11/20/2015

<b>Reactivity:</b>	Not classified as a reactivity hazard.
<b>Chemical stability:</b>	Stable under normal conditions.
<b>Possibility of hazardous reactions:</b>	Use at elevated temperatures may form highly hazardous compounds. At above 150°C (300°F) in the presence of air, trace quantities of formaldehyde may be released. Acetic acid is formed upon contact with water or humid air.
<b>Conditions to avoid:</b>	Moisture and incompatible materials.
<b>Incompatible materials:</b>	Strong oxidizing agents or electrophiles (e.g. ferric chloride). Concentrated acids or bases can degrade the silicone polymer.
<b>Hazardous decomposition products:</b>	Carbon oxides, silicone dioxide, metal oxides, formaldehyde and traces of incompletely burned carbon products.

### SECTION 11 - TOXICOLOGICAL INFORMATION

#### INFORMATION ON THE LIKELY ROUTES OF EXPOSURE:

<b>Inhalation:</b>	Prolonged inhalation may be harmful.
<b>Ingestion:</b>	May be harmful if swallowed.
<b>Skin contact:</b>	May cause skin irritation on direct contact.
<b>Eye contact:</b>	May cause eye irritation on direct contact.

**Symptoms related to the physical, chemical and toxicological characteristics:** Acetic acid vapors may irritate eyes, nose and throat. Direct contact with eyes and skin will irritate.

#### ACUTE TOXICITY:

Ingredient Name	Result	Species	Dose	Exposure
Silicone Dioxide	LD50 Oral	Rat	>3,300 mg/kg	----
	LC50 Inhalation	Rat	>2.08 mg/L	4 hours
	LD50 Dermal	Rabbit	>5,000 mg/kg	----
Distillates (petroleum), Hydrotreated Middle	LD50 Oral	Rat	5,000 mg/kg	----
	LC50 Inhalation	Rat	1.78 mg/L	4 hours
	LD50 Dermal	Rat	>2,000 mg/kg	----

<b>Skin corrosion/irritation:</b>	Not classified based on available information.
<b>Serious eye damage/irritation:</b>	Not classified based on available information.
<b>Aspiration hazard:</b>	Not classified based on available information. Distillates (petroleum), hydrotreated middle (CAS# 64742-46-7) is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.
<b>Specific target organ toxicity – single exposure:</b>	Not classified based on available information.
<b>Specific target organ toxicity – repeated exposure:</b>	Not classified based on available information.
<b>Respiratory or skin sensitization:</b>	Not classified based on available information.
<b>Carcinogenicity:</b>	No ingredients of this product present at levels greater than or equal to 0.1% is considered by IARC, NTP or OSHA to be carcinogens.

## SB-188 HIGH TEMPERATURE SILICONE SEALANT (CLEAR)

**Reproductive toxicity:** Not classified based on available information.  
**Teratogenicity:** Not classified based on available information.  
**Germ-cell mutagenicity:** Not classified based on available information.

Page Number: 5/6  
 Revision Date: 11/20/2015

### SECTION 12 - ECOLOGICAL INFORMATION

**Ecotoxicity:** No data available.  
**Persistence and degradability:** No data available.  
**Bioaccumulative potential:** No data available.  
**Mobility in soil:** No data available.  
**Other adverse effects:** No data available.

### SECTION 13 - DISPOSAL CONSIDERATIONS

**Disposal instructions:** This product has been evaluated for Resource Conservation and Recovery Act (RCRA) characteristics and does not meet the criteria of hazardous waste if discarded in its purchased form. Dispose of contents/container in accordance with local, regional, national and international regulations.

**Waste from residues:** Dispose of in accordance with local regulations.

**Contaminated packaging:** Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal.

### SECTION 14 - TRANSPORT INFORMATION

**Shipping Information:** Not subject to DOT, TDG, IMDG Code or IATA Regulations.

### SECTION 15 - REGULATORY INFORMATION

**EPCRA – Emergency Planning and Community Right-to-Know**

**CERCLA Reportable Quantity:**

Ingredients	CAS No.	Component RQ (lbs)	Calculated product RQ (lbs)
Acetic acid	64-19-7	5000	*
Acetic anhydride	108-24-7	5000	*

\* Calculated RQ exceeds reasonably attainable upper limit.

**SARA 304 Extremely Hazardous Substances Reportable Quantity:** This product does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards:** No SARA hazards.

**SARA 302:** No chemicals in this product are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313:** This product does not contain any chemical components with known CAS No. that exceed the threshold reporting levels established by SARA Title III, Section 313.

**Pennsylvania Right To Know:**

Dimethyl siloxane, hydroxy-terminated	70131-67-8	70 – 90%
Silicone dioxide	7631-86-9	5 – 10%
Distillates (petroleum), hydrotreated middle	64742-46-7	5 – 10%
Acetic acid	64-19-7	0 – 0.1%
Acetic anhydride	108-24-7	0 – 0.1%

## SB-188 HIGH TEMPERATURE SILICONE SEALANT (CLEAR)

### New Jersey Right To Know:

Dimethyl siloxane, hydroxy-terminated	70131-67-8	70 – 90%
Silicone dioxide	7631-86-9	5 – 10%
Distillates (petroleum), hydrotreated middle	64742-46-7	5 – 10%

Page Number: 6/6  
Revision Date: 11/20/2015

**California Proposition 65:** This product does not contain any chemicals known to State of California to cause cancer, birth or any other reproductive defects.

### The ingredients of this product are reported in the following inventories:

**TSCA:** All chemical substances in this product are included on or exempted from listing on the TSCA inventory of Chemical Substances.

**DSL:** All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempted from listing on the Canadian Domestic Substances List (DSL).

**NFPA Profile:** Health 1, Flammability 1, Reactivity 0

## SECTION 16 - OTHER INFORMATION

**DISCLAIMER:** The information contained herein is based on data available as of the date of preparation of this SDS and which we believe to be reliable. However, no warranty is expressed or implied regarding the accuracy of the data. We shall not be responsible for the use of this information, or of any product, method or apparatus mentioned. User must make his/her own investigation to determine the suitability of the information or products for his/her particular purpose, for the protection of the environment and the health and safety of the users of this material.